



R

**OPERATING LIMITS**

Pressure: 1 MPa

Speed: 15 m/s

Temperature: -30 °C ~ 200 °C



Type	d1	d3	d7	L1	L3
P10R	10	20	18.1	20.5	5.5
P12R	12	22	20.6	23.5	5.5
P13R	13	25	23.1	28	6
P14R	14	25	23.1	28	6
P15R	15	29	26.9	30	7
P16R	16	29	26.9	30	7
P17R	17	29	26.9	30	7
P18R	18	33	30.9	32	8
P19R	19	33	30.9	33	8
P20R	20	33	30.9	33	8
P21R	21	38	35.4	33	8
P22R	22	38	35.4	33	8
P24R	24	38	35.4	35	8
P25R	25	40	38.2	35.5	8.5
P28R	28	46	43.3	39	9
P30R	30	46	43.3	39	9
P32R	32	46	43.3	39	9
P35R	35	50	53.5	50.5	11.5
P38R	38	58	60.5	50.5	11.5
P40R	40	58	60.5	50.5	11.5

- Stationary Ring (Ceramic/SiC/TC)
- Rotary Ring (Carbon/ SiC/TC)
- Secondary Seal (NBR/ EPDM/VITON)
- Spring & Other Parts (S.S/SUS304/SUS316)

